INTERACTIVE BOARD SCR-PR

	Image							
Display Parameters	Product Size	55 inch	65 inch	75 inch	86 inch	98 inch	100 inch	110 inch
	Backlight Type	DLED Backlight						
	Display Area	1209.6x680.4 mm	1429.3x804.9 mm	1650x929 mm	1895.2x1065.6 mm	2158.85x1214.35 mm	2204.1x1240.1 mm	2440.6x1371.6 mm
	Resolution	4K(3840x2160)						
	Brightness	500cd/m2 ± 20						
	Contrast	5000 : 1						
	Visual Angle	H/V : 178°/178°						
	Aspect Ratio	16 : 9						
	Display Color	10Bit,1.07B						
	Life (hrs)	≥60,000(hrs)						
	Bonding	Zero gap						
	Eye Saver Mode	Flicker free + Low Blue Light						
	Surface Hardness	3.2 mm ≥ 7H						
Touch Screen Parameters	Touch Surface	High explosion-proof tempered glass (Anti-glare glass Optional)						
	Touch Scheme	non-contact high-precision infrared sensing technology						
	Touch Points	50 Points Infrared Touch Recognition						
	Responding Speed	Single point model : Click 8 ms, continuous 3 ms / Multipoint model : Click 8 ms, continuous 5-8 ms						
	Touch Accuracy	≤ 1mm						
	Input Method	Fingers, stylus or any other opaque material medium						
	Communication	USB2.0/3.0 (Full speed)						
	Stability	No drift, strong ability to adapt to environmental changes						
	Anti-Light Interference	The light illuminates the screen at various angles and can be used normally						
	Output Method	Coordinate						
Android Operating System	OS Version	Android 13.0						
	Main Chip Model(Processor)	RK 3588						
	CPU	Octa-core A76*4 + A55*4 , 2.2GHz						
	GPU	Mali-G610 MC4_700MHz						
	RAM (DDR4)	16 GB (Built-in)						
	ROM (EMMC5.1)	256 GB (Built-in)						
Languages	OSD Languages	Chinese, English,French, Spanish, Portuguese, Russian, Arabic, Italy, Korean,Japanese, Vietnamese 29 Languages						
Interface (Terminals)	Front Interface	USB 3.0*2						
		HDMI IN *1						
		Type-C*1						
		Touch Out*1						
	Side interface	HDMI IN *3						
		USB 3.0*3						
		Type-C*1 (Normal 65 W, Customizlation 100 W)						
		TF Card*1						
		Touch USB 3.0*3						
		DP*1						

INTERACTIVE BOARD SCR-PR

	Image							
Interface (Terminals)	Bottom interface	55 inch	65 inch	75 inch	86 inch	98 inch	100 inch	110 inch
		RS232 *1						
		RJ45 IN*1 + RJ45 OUT*1						
		MIC *1 +VGA Audio IN*1						
		Audio Line OUT *1						
		HDMI Out*1						
		Coaxial Out*1						
		Type-C OUT *1 5W						
		VGA IN*1						
WiFi and Bluetooth	WIFI	2.4G+5G WIFI 6						
	Bluetooth	Bluetooth 5.2						
Speakers	Output Power (build in)	2x20W+20W - HIFI stereo sound with improved bass response						
Camera and Array - Microphone	Camera (build in)	Super High Resolution 13 Million Pixels						
		Support Dual System Following Recognition						
	Array-Microphone (build in)	Built-in 8Array Omnidirectional Microphones						
		8-12Meters Microphone Reception Distance						
NFC	NFC Tag Reader (build in)	NFC Reader for locking and unlocking the screen/Mirror						
		IR Recevier						
USB Media Display	Video	H263, H264, H265, MPEG2, MPEG4, VC1, VP6, VP8, VP9, MJPEG, AVS, AVS+, AVS2, mp4						
	Music	MP3, WAV, AAC, AC3, EAC3, Vorbis, FLAC, APE, TrueHD, DTS, DTSHD						
	Picture	jpeg, .bmp, .png, gif						
	Storage	NTFS, FAT32, FAT16						
Power Supply	Input	AC 100-240V 50/60Hz						
	Consumption	≤160W	≤ 350W				≤ 450W	≤ 600W
	Standby Power	≤ 0.5W						
Temperature / Humidity	Working Temperature	0˚C ～ 40˚C						
	Storage Temperature	-20˚C ～ 60˚C						
	Storage Humidity	10%～90% RH Non-Condensing						
	Working Humidity	10%～80% RH Non-Condensing						
Packing Details	Standard Accessories	Writing Pen(Stylus), Remote Control, AC Power Cord, Wall Mount, User Manual etc.						
	Product Dimension	1282*774*87mm	1501*897*87 mm	1726*1041.2*92.1 mm	1968*1177.5*92.9 mm	2217*1313.5*103.2 mm	2268.7*1342.7*117.5 mm	2505x1474x100.8 mm
	VESA	L400*V300 mm		L600*V500 mm	L600*V600 mm	L800*V400 mm		L800*V800 mm
	Package Dimension	L1395*W190*H910mm	L1645*W210*H1025mm	L1870*W225*H1180mm	L2110*W225*H1325mm	L 2360*W 220*H 1450mm	L 2430*W 250*H 1530mm	L 2665*W 245*H 1670MM
	N.W/G.W	23.5 kg / 29.6 kg	30.6 kg / 39.1 kg	43.2 kg / 55.3 kg	62.7 kg / 71.1 kg	89.1 kg / 110 kg		116.5 kg / 156 kg
Export Certification	Certificates	FC CE RoHS COMPLIANT						